



Product Code: MI-IN-D-2-L (Internal Sensor)
MI-0E-D-2-L (External Sensor)
Multi-trip Logger

www.escortdls.com

- Large LCD display with multi function viewing
- Available with either Internal or External sensor options
- Customisable alarm settings and programmable start function
- Downloadable via a USB to Serial Port cable, no interface required
- Provides maximum data logging reliability and accuracy at a low cost
- User-friendly multi-language software for easy programming and download

Affordable Assurance



www.escortdls.com

Intelligent Mini Specifications

| | |
|-----------------------------|--|
| Product Code | MI-IN-D-2-L or MI-OE-D-2-L |
| Temperature Range | Measuring -40°C to +65°C (-40°F to 149°F) |
| Sensors | Internal or external options |
| Accuracy | ± 0.5°C (1.0°F) |
| Resolution | 0.5°C (1.0°F) |
| Sensor response time | Internal Sensor – T90 of 20 minutes in moving air External Sensor – T90 of 5 minutes |
| Memory | 1868 samples |
| Software | ESCORT Console (free to download via our website) |
| Sampling Frequency | 1 to 255 minutes |
| Time and date | Real time clock, accuracy better than 1 minute per month at ambient Multiple time zones supported |
| Security | Password protected (programmable using Escort Console software) |
| Power Source | User replaceable 3V 550 mA AH Lithium coin cell battery |
| IP Rating | IP51 (with DB9 cap on) |
| Size | 80 x 57 x 20mm (excluding lug) |
| Weight | 70 grams (including battery) |
| Case Material | Polycarbonate/ABS |
| Storage Temperature | -40°C to +85°C (-40°F to 185°F) |
| Typical battery life | 1 to 2 years |
| Recorder start-up | Long button press |
| Warranty | 24 months, excluding battery |



LCD displays highest recorded reading



LCD displays lowest recorded reading



LCD displays the average reading for the current trip



LCD displays the time above the specified high alarm setting for the current trip



LCD displays the time below the specified low alarm setting for the current trip