

# Product Specifications

## FlashLink Certified Alarm Thermometer

<b>Internal Sensor Range</b>	14°F to 122°F (-10°C to 50°C)
<b>External Probe Range</b>	-58°F to 158°F (-50°C to 70°C)
<b>Accuracy</b>	±1.0°F from 14°F to 77°F (±.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C)
<b>Sampling Rate</b>	10 seconds
<b>Display Resolution</b>	0.1°F/°C
<b>Display Size</b>	1.8in W x 0.87in H (46mm W x 22mm H)
<b>Instrument Size</b>	3.15in W x 2.05in H x 0.67in D (80mm W x 52mm H x 17mm D)
<b>External Probe Type/Size</b>	Stainless Steel, 0.7in L x 0.2in Dia (17.8mm L x 5mm Dia)
<b>External Sensor Bottle</b>	Polystyrene with PE cap, 1.6in L x 0.79in Dia (41mm L x 20mm Dia)
<b>External Sensor Buffer</b>	Propylene glycol (GRAS classified – Generally Recognized As Safe)
<b>External Sensor Cable</b>	9.84ft x 0.08in Dia (3 meters x 2mm Dia)
<b>Battery</b>	Coin Cell Lithium Battery
<b>Certification</b>	CE mark, NIST traceable, WEEE



### Models

<b>12215</b>	Includes Manufacturer's Certificate of Compliance traceable to NIST
<b>12224</b>	Includes NIST Calibration Certificate & Manufacturer's Certificate of Compliance
<b>12225</b>	Includes ISO 17025 Calibration Certificate & Manufacturer's Certificate of Compliance

- Ideal for monitoring vaccines and common fluids stored in refrigerators, freezers, and cold holding display cases
- Internal sensor for ambient air temperature
- External sensor with high/low alarm setting
- Switchable internal/external temperature display
- Glycol buffered probe emulates products and prevents false alarms during normal use
- Minimum/Maximum memory stores lowest/highest readings
- Audible alarm for temperature excursions
- Jumbo LCD with back light
- Switchable °F/°C scale
- Magnetic attachment and fold-away stand

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0122 15B1

